

Wyoming Analytical Laboratories, Inc. Prices as of Spring, 2009



This electronic price book is a general guideline to WAL prices. Please call for specific price quotes.

Table of Contents

Click on topic to jump to analysis type.

Use Adobe “binocular icon” to search.

GENERAL INFORMATION	3
CEMENT & FLY ASH	4
SOIL & OVERBURDEN	5
ELEMENTAL ANALYSIS.....	6
GENERAL CHAIN OF CUSTODY / SERVICE REQUEST.....	7
CONTAINERS, PRESERVATIVES & HOLDING TIMES	8
USEFUL CONVERSIONS AND DEFINITIONS	10

GENERAL INFORMATION

1660 Harrison Street
Laramie, WY 82070
(307)742-7995
Fax: (307) 721-8956

625 Center Street
Rock Springs, WY 82901
(307) 362-3176
Fax: (307) 362-3581

14335 West 44th Ave.
Golden, CO 80403
(303) 278-2446
Fax: (303) 278-2439

Normally samples may be submitted to any of our locations.

Standard turn-around-times (TAT) are 10 working days, expedited TAT can usually be honored for a premium.

If you require a quick TAT, check with the lab facility to verify that the current work-load will allow for rush samples.

If the lab can honor your request for quick TAT, premiums can then be agreed upon .

Premiums for accelerated work are as follows:

For same day turnaround, add 300%

1 working day, add 100%

4-5 working days, add 30%

2-3 working days, add 50%

6-7 working days, add 15%

The Following terms and conditions will apply to all goods and services by
Wyoming Analytical Laboratories, Inc. (WAL)

Payment in full is due upon receipt of invoice, or as specified in prearranged terms

1. WAL reserves the right to terminate the customer's credit and refuse to perform additional services on a credit basis if any credit balance is outstanding for more than 60 days or when any amount exceeds the established line of credit.
2. Prices quoted to the customer will remain effective for 90 days unless otherwise stated in writing by WAL at the time of quotation.
3. Any schedule of fees and changes issued by WAL may be changed from time to time by WAL as to future services.
4. The analyses, opinions or interpretation of results by WAL, in response to a customer request upon observation of materials provided by the customer and express the best judgment of WAL. WAL will endeavor to perform its services and report accurate and complete results, all in accordance with standards and practices of the industry. WAL does not guarantee results and its sole liability will be to redo the test and render a new report to the customer any payment made by the customer for a report which does not meet industry standards or practices.
5. WAL will hold in confidence all information it receives from the customer and the results of all tests and other services provided to the customer.

EXCEPT AS NOTED ABOVE, WAL MAKES NO REPRESENTATION OR WARRANTY, EXPRESS IMPLIED OR STATUTORY, REGARDING ITS SERVICES, OBTAINED OR ITS REPORT

CEMENT & FLY ASH

Cement, Concrete, Aggregate	Method	Price
Cement – Elemental Analysis: SiO ₂ , Al ₂ O ₃ , Fe ₂ O ₃ , TiO ₂ , CaO, MgO, Na ₂ O, K ₂ O, P ₂ O ₅ , Mn ₂ O ₃ , SrO, BaO, SO ₃ , LOI, Insoluble Residue	ASTM C-114 (XRF)	\$260.00
Insoluble Residue	ASTM C-114	\$ 33.00
Chloride, Total	ASTM C-1218	\$ 38.00
Chloride, Water Soluble	ASTM D-1411	\$38.00
Cement Content of Concrete	ASTM C-1084	\$550.00
Free Calcium Oxide (CaO)	ASTM C-114	\$ 73.00
Lightweight Concrete-Aggregate	ASTM C-123	\$ 73.00
Staining Materials in Lightweight Concrete-Aggregate	ASTM C-641	\$83.00

Fly Ash and Other Pozzolans – ASTM D-4326	Method	Price
Sample Preparation		\$45.00
Elemental Analysis: SiO ₂ , Al ₂ O ₃ , Fe ₂ O ₃ , TiO ₂ , CaO, MgO, Na ₂ O, K ₂ O, P ₂ O ₅ , Mn ₂ O ₃ , SrO, BaO, SO ₃ , LOI, Moisture	ASTM D-4326	\$195.00
Individual Elements from Above List- per Element, + Sample Prep Fee		\$ 40.00
Other Elements- by Request		Inquire

28-Day – Available Alkali	Method	Price
Determination of Sodium and Potassium in Solution	ASTM C-311	\$ 55.00

Limestone (Gypsum)	Method	Price
LOI (1000° C), Moisture (120° C), Elemental Analysis (MnO ₂ , SiO ₂ , Al ₂ O ₃ , Fe ₂ O ₃ , CaCO ₃ , MgO, SO ₃ , K ₂ O, P ₂ O ₅ , SrO, BaO)	ASTM C-25	\$260.00
Acid Insolubles	ASTM C-25	\$45.00

Available Lime Index	Method	Price
	ASTM C-25	\$ 75.00

Cement and fly ash samples are analyzed at the Denver Division in Golden, Colorado. It would, therefore, be expedient to submit these types of samples directly to that location. (WAL / Denver Division, 1511 Washington Avenue, Golden, Colorado 80401). WAL will, of course, accept samples at any of our locations and direct them to the appropriate facility as necessary.

SOIL & OVERBURDEN

Preparation	Price
Splitting & blending fee	16.00
Acid digestion fee , (required for total metals)	59.00
Bomb digestion fee (required for total Lead, Arsenic or Selenium)	38.00
DTPA extraction for metals	14.00

Determination	Price
pH (saturated paste)	\$ 14.00
Conductivity	8.00
Saturation percentage	8.00
Particle Size analysis	
Clay, silt, sand, very fine sand	38.00
Clay, silt, sand	32.00
Texture (requires particle size analysis)	4.00
Soluble cations (calcium, magnesium, sodium, potassium)	27.00
Soluble anions	58.00
Sodium Absorption Ratio (SAR) (requires soluble cations)	8.00
Exchangeable Cations (requires soluble cations and anions)	58.00
Exchangeable Sodium % (ESP) (requires SAR)	8.00
Acid-base potential (ABP=NP-AP)	54.00
Acid potential (AP=ST-SS04)	43.00
Neutralization potential (as % CaCO ₃)	11.00
Nitrate nitrogen	30.00
Organic matter	22.00
Organic carbon	49.00
Carbonates	16.00
Coarse Fragment	10.00
Arsenic (As)	38.00
Boron (B)	22.00
Copper (Cu)	27.00
Chromium, hexavalent (Cr ⁺⁶ ; Cr ^{IV})	40.00
Lead (Pb)	38.00
Molybdenum (Mo)	11.00
Selenium (Se)	38.00
Sulfur, total (S _T)	27.00
Sulfate sulfur (S _{SO4})	16.00
Total Organic Carbon (TOC) Method 415.1	46.00
Total recoverable petroleum hydrocarbons (TRPH) Method 418.1	165.00
BTEX Method SW-846 8260	95.00
Methanol	125.00
Glycols	110.00
Qualitative XRF scan , 10 most abundant elements	128.00

ELEMENTAL ANALYSIS

By X-Ray Fluorescence Spectrometry (XRF)

X-Ray Fluorescence Spectrometry (XRF) allows direct analysis of solid samples. The method gives a highly accurate analysis of major and minor components, and is also capable of determining trace elements down to 5 to 10 ppm. XRF is also a very effective way to do a complete elemental scan of an unknown sample; it is able to scan all elements heavier than Sodium.

Coal / Petroleum Products	Method	Price
Sample Preparation		\$ 15.00
Chlorine (Cl)		\$ 30.00
Bromine (Br)		\$ 30.00
Iodine (I)		\$ 30.00
Sulfur (S)		\$ 35.00
Other Elements		Inquire

Analysis of Coal Ash and Fly Ash	Method	Price
Preparation of Ash		\$ 35.00
Elemental Analysis: (reported as the oxides) SiO ₃ , TiO ₂ , Al ₂ O ₃ , Fe ₂ O ₃ , CaO, MgO, K ₂ O, Na ₂ O, P ₂ O ₅ , MnO ₂ , SrO, BaO, SO ₃ ; Alkalies as Na ₂ O; Calculated Base/Acid Ratio, Silica Ratio, and T ₂₅₀ .	ASTM D-4326	\$185.00

Petroleum Coke		Price
Sample Preparation		\$ 35.00
Silicon (Si), Calcium (Ca), Iron (Fe), Nickel (Ni), Vanadium (V), Sulfur (S) Includes Preparation Fee		\$130.00
Individual Elements for Above List + Sample Preparation Fee		\$ 35.00
Other Elements by Request		Inquire

Petroleum Products		Price
Sample Preparation		\$ 35.00
Vanadium (V), Nickel (Ni), Iron (Fe), per element		\$ 20.00
Sulfur (S)		\$ 35.00
Other Elements by Request		Inquire

Rock, Soil and Clay		Price
Elemental Analysis (reported as the oxides) SiO ₃ , Al ₂ O ₃ , Fe ₂ O ₃ , CaO, MgO, Na ₂ O, K ₂ O, TiO ₂ , MnO ₂ , P ₂ O ₅ , SrO, BaO; (also includes loss on ignition and moisture)		\$195.00
Single Elements from List + \$35.00 Prep Fee		\$35.00

Qualitative Scan		Price
Qualitative Scan for Major and Minor Elements		\$ 95.00
Quantification of Elements Found		\$150.00

Silica and Alkali Reactivity		Price
ASTM C-289		\$110.00

General Chain of Custody / Service Request

Wyoming Analytical Laboratories, Inc.

1660 Harrison Street
Laramie, WY 82070
(307) 742-7995
Fax: (307) 721-8956

625 Center Street
Rock Springs, WY 82901
(307) 362-3176
Fax: (307) 362-3581

1511 Washington Ave
Golden, CO 80401
(303) 278-2446
Fax: (303) 278-2439

Project:	Billing Information
Send Report to:	Name:
Address:	Company Name:
City: State: Zip:	Address:
Phone:	City: State: Zip:
Fax:	Phone: Fax:
E-mail:	E-mail Results: Yes / No
PO Number:	Fax Results: Yes / No

Sample Identification	Matrix *	El. Analysis	pH					Total number of Samples _____	Date/Time	Special Instructions

*Matrix: C-Coal; A-Ash; S-Soil; W-Water; X-other, (please specify) _____

Sample Transfer Record (1)

Sample Transfer Record (2)

Relinquished by: _____
Signature: _____
Date: _____

Relinquished by: _____
Signature: _____
Date: _____

Received by: _____
Signature: _____
Date: _____

Received by: _____
Signature: _____
Date: _____

Please make photocopies of this form to accompany samples submitted to WAL for analysis.

CONTAINERS, PRESERVATIVES & HOLDING TIMES

Metals

Analyte	Method	Container	Preservative	Holding Time
<u>Metals, dissolved</u>				
Metals	SW-846 / 600 series	1 - 250mL poly	Field filter	180/28 days
8 RCRA, 13 Priority Pollutants	SW-846 / 600 series	1 - 500mL poly	Field filter	180/28 days
23 HSL	SW-846 / 600 series	1 -1L poly	Filed filter	180/28 days
Hexavalent Chromium	SM3500 CR-D	1 - 500mL poly	4°C	24 hours
<u>Metals, total, total recoverable</u>				
Metals	SW-846 / 600 series	1-250mL poly	2mL 1:1 HNO ₃	180/28 days
8 RCRA, 13 Priority Pollutants	SW-846 / 600 series	1-500mL poly	2mL 1:1 HNO ₃	180/28 days
23 HSL	SW-846 / 600 series	1-1L poly	5mL 1:1 HNO ₃	180/28 days

Water

Analyte	Method	Container	Preservative	Holding Time
Alkalinity / CO ₂ / HCO ₃ or Acidity	310.1 or 305.1	1 - 125mL poly	4°C	14 days
Ammonia	SM4500-NH3F	1 - 500mL poly	4°C, 2mL 1:1 H ₂ SO ₄	28 days
Anions - NO ₂ , NO ₃ , PO, SO ₄ , Br, Cl	300 (IC method)	1 - 125mL poly	4°C	2/28 days
BOD	405.1	1 - 1L poly	4°C	48 hours
BTEX / MTBE / Purgeable Aromatics	8020 / 624	2 - 40mL vials	4°C, 0.5mL 1:1 HCl	14 days
Carbamates	632	1 - 1L amber	4°C	7 days
COD	410.4	1 - 125mL amber	4°C, 2mL 1:1 H ₂ SO ₄	28 days
Coliform – Fecal & Total (drinking water)	Colilert	1 - 110mL, sterile	4°C -Na ₂ S ₂ O ₃	24 hours
Color	110.2	1 - 125mL amber	4°C	48 hours
Cyanide – Total, WAD, Amenable	335.1 / .2 / 9010	1 - 1L poly	4°C, 10mL 10N NaOH	14 days
Dissolved Oxygen	360.1	BOD Bottle	4°C	24 hours
Flashpoint	1010 / ASTM D-93	1 - 250mL amber	4°C	28 days
Fluoride	340.2	1 - 125mL poly	4°C	28 days
Formaldehyde	8315	1 - 1L amber	4°C	3 days
Glycol / Alcohol	8015	1 - 20mL vial	4°C	14 days
Herbicides	8150	1 - 80oz amber	4°C	7 days
Ignitability	1010	1 - 250mL glass	4°C	28 days
Langelier Index	SM2330B	1 - 1L poly	4°C	ASAP
Nitrate/Nitrite		1 - 125mL poly	4°C, H ₂ SO ₄	28 days
Odor	140.1	1 - 1L amber	4°C	48 hours
Oil & Grease	1664	1 - 1L amber	4°C, 5mL 1:1 H ₂ SO ₄	28 days
Pesticides / PCBs	8080/608 or 8140	1 - 80oz amber	4°C	7 days
PCB Screen	8080 mod.	1 - 125mL amber	4°C	7 days
pH – corrosivity	150.1	1 - 125mL poly	4°C	ASAP
Phenols, Total	420.1	1 - 1L amber	4°C, 5mL 1:1 H ₂ SO ₄	28 days
Phenols	8040	1 - 80oz amber	4°C	7 days
Purgeable Halocarbons	8260 / 624	2 - 40mL vials	4°C	14 days
Reactivity – CN, Sulfide	SW846	1 - 250mL poly	4°C, 2mL 10N Zn acetate	7 days
Residual Chlorine	330.5	1 - 250mL amber	4°C	24 hours
Semi-volatiles (BNA/PNA)	8270 / 625	1 - 80oz amber	4°C	5 days
Specific Conductance	120.1 / 9050	1 - 125mL poly	4°C	28 days
Sulfide	376.1 / 9030	1 - 500mL poly	4°C, 5mL 10N Zn acetate	7 days
Sulfite	377.1	1 - 500mL poly	4°C, 0.5g Zn acetate, 5mL EDTA	7 days
Surfactants (MBAS)	425.1	1 -1L poly	4°C	48 hours
TCLP BNA, Pest, Herb, Metals	1311 / SW846	1 - 80oz amber	4°C	14 days
TCLP Metals	1311 / 6010,7470	1 - 1L poly	4°C	180/28 days
TCLP VOA	1311 / 8260	1 - 250mL amber	4°C	14 days
TEPH (Diesel) Fuel ID / DRO	8015 mod	1 - 1L amber	4°C	7 days
TVPH (Gasoline)	8015 mod	2 - 40mL vials	4°C, 0.5mL 1:1 HCl	14 days
Total Organic Carbon-TOC	9060 / 415.1	1 - 125mL amber	4°C, 2mL 1:1 H ₂ SO ₄	28 days
Total Organic Halogens-TOX	9020	1 - 500mL amber	4°C, 3mL 1:1 H ₂ SO ₄	28 days
Total Halogens – TX (oil)	9020 mod	1 - 20mL vial	4°C	none
TRPH	418.1	1 - 1L amber	4°C, 5mL 1:1 HCl	28 days
TS/TDS/TSS	160.1 / .2	1 - 500mL poly	4°C	7 days
Turbidity	180.1	1 - 125mL poly	4°C	48 hours
VOAs	8260 / 624	2 - 40mL vials	4°C, 0.5mL 1:1 HCl	14 days

Drinking Water

Analyte	EPA Method	Container	Preservative	Holding Time
VOC / Trihalomethanes	524.2	4-40mL vials	4°C 20mg ascorbic acid, add	14 days
SOC	525.1	1-1L amber	4°C 55mg Na ₂ SO ₃ +HCl	7 days
Nitrogen / Phosphorus Pesticides	507	1-1L amber	4°C 80mg Na ₂ S ₂ O ₃	7 days
Pesticides / PCBs	508	1-1L amber	4°C 80mg Na ₂ S ₂ O ₃	7 days
Herbicides	515	1-1L amber	4°C 80mg Na ₂ S ₂ O ₃	14 days
EDB / DBCP	504	2-40mL vials	4°C 3mg Na ₂ S ₂ O ₃	28 days
Carbamates	531.1	1-125mL amber	4°C 10mg Na ₂ S ₂ O ₃ +MCAA	28 days
Diquat	549	1-500mL polyamber	4°C 50mg Na ₂ S ₂ O ₃	7 days
Endothal	548	1-125mL amber	4°C	7 days
Glyphosate	547 mod	1-125mL amber	4°C 12mg Na ₂ S ₂ O ₃	14 days
Lead and Copper Rule	239.2 / 200.7	1-1L poly	5mL 1:1 HNO ₃ (unpreserved if a private residence)	180 days

Soil

Analyte	Method	Container	Preservative	Holding Time
Anions - Br, Cl, NO ₂ , NO ₃ , PO ₄ , SO ₄	300.0	1-2oz wm	4°C	28 days
BTEX / MTBE / Purgeable Aromatics	8020	2-2oz wm	4°C	14 days
Corrosivity / pH	150.1	1-2oz wm	4°C	14 days
Cyanide	335.2	1-2oz wm	4°C	28 days
Extractable Organic Halogens – EOX	9020 mod	1-2oz wm	4°C	28 days
Herbicides	8150	1-4oz wm	4°C	14 days
Ignitability / Flashpoint	1010 / ASTM D93	1-8oz wm	4°C	28 days
Oil and Grease	413.1	1-4oz wm	4°C	28 days
Paint Filter Test	9095	1-4oz wm	4°C	28 days
Pesticides / PCBs	8080 or 8140	1-4oz wm	4°C	14 days
Phenols (Total)	420.1	1-4oz wm	4°C	14 days
Reactivity	SW846	1-2oz wm	4°C	28 days
Semi-volatiles (BNA, PNA)	8270	1-4oz wm	4°C	14 days
TCLP Volatiles	1311 / 8260	1-4oz wm	4°C	14 days
TCLP BNA, Pest, Herb	1311 / 8270, 8080, 8150	1-6oz wm	4°C	14 days
TCLP Metals	1311 / 6010, 7470	1-4oz wm	4°C	180 days
TEPH (Diesel) / Fuel ID / DRO	8015 mod	1-2oz wm	4°C	14 days
Total Metals	6010 / 7471	1-2oz wm	4°C	80/28 days
TRPH	418.1	1-4oz wm	4°C	28 days
TVPH (Gasoline)	8015 mod	1-2oz wm	4°C	14 days
VOA or Purgeable Halocarbons	8260 or 8010	1-2oz wm	4°C	14 days

(wm = wide-mouthed, glass jar)

Radiochemistry

Analyte	Method	Container	Preservative	Holding Time
Gross Alpha, Beta	EPA 900.0	1 - 1L poly	5mL 1:1 HNO ₂	180 days
Ra-226	SM7500 RaB mod	1 - 1L poly	5mL 1:1 HNO ₂	180 days
Ra-228	EPA Ra 05	1 - 1L poly	5mL 1:1 HNO ₃	180 days
Uranium	ASTM D2907	1 - 1L poly	5mL 1:1 HNO ₃	180 days
Radon	EPA 600 / 2-87 / 082	2 - 40mL vials	4°C	48 hours

USEFUL CONVERSIONS AND DEFINITIONS

Water related conversions:

1 ppm (liquid) = 1 mg/L = 1000 µg/L = 1000 ppb (liquid)

1 ppm (solid) = 1 mg/kg = 1000 µg/kg = 1000 ppb (solid)

1% = 10,000 ppm

1 gallon water = 231 cubic inches = 8.333 pounds

Water Hardness is given by the following formula:

Hardness, as mg/L CaCO₃ = 2.497 x Ca, mg/L + 4.115 x Mg, mg/L

1 mg/L CaCO₃ = 0.058 grains/Gallon (US)

Definitions

Metals, Analyte types

Dissolved Analyte – The concentration of analyte in an aqueous sample that will pass through a 0.45 µm membrane filter assembly prior to sample acidification.

Suspended Analyte – Those elements which are retained by a 0.45 µm membrane filter.

Total – The concentration determined on an unfiltered sample following vigorous digestion

Total Recoverable Analyte – The concentration of analyte determined either by "direct analysis" of an unfiltered, acid-preserved drinking water sample with turbidity of <1 NTU, or by analysis of the solution extract of a solid sample or an unfiltered aqueous sample following digestion by refluxing with hot dilute mineral acid(s) as specified in the method.

Potentially Dissolved Analyte – The concentration of analyte in an acidified aqueous sample that will pass through a 0.45 µm membrane filter after acidification for 8 – 9 hours. (This definition is only used by State of Colorado.)

TCLP – Toxicity Characterization Leaching Procedure (EPA SW-846 1311) – this is a leach procedure that is designed to give the mobile fraction of the metals in the sample and not the content of the metals in the sample. It is often incorrectly used to refer to the 8 RCRA metals that are most commonly extracted with this procedure.

Data Quality Objective (DQO) – Client-defined quality parameters, such as project-specific detection levels, RPD.

Field Reagent Blank (FRB) – An aliquot of reagent water or other blank matrix that is placed in a sample container in the laboratory and treated as a sample in all respects, including shipment to the sampling site, exposure to the sampling site conditions, storage, preservation, and all analytical procedures. The purpose of the FRB is to determine if method analytes or other interferences are present in the field environment.

Laboratory control sample (LCS): A volume of reagent water spiked with known concentrations of analytes and carried through the preparation and analysis procedure as a sample. It is used to monitor loss/recovery values.

Laboratory Duplicates (LD1 and LD2) – Two aliquots of the same sample taken in the laboratory and analyzed separately with identical procedures. Analyses of LD1 and LD2 indicate precision associated with laboratory procedures, but not with sample collection, preservation, or storage procedures.

Laboratory Fortified Sample Matrix (LFM) – An aliquot of an environmental sample to which known quantities of the method analytes are added in the laboratory. The LFM is analyzed exactly like a sample, and its purpose is to determine whether the sample matrix contributes bias to the analytical results. The background concentrations of the analytes in the sample matrix must be determined in a separate aliquot and the measured values in the LFM corrected for background concentrations.

Laboratory Reagent Blank (LRB) – An aliquot of reagent water or other blank matrices that are treated exactly as a sample including exposure to all glassware, equipment, solvents, reagents, and internal standards that are used with other samples. The LRB is used to determine if method analytes or other interferences are present in the laboratory environment, reagents, or apparatus

Method blank: A volume of reagent water processed through each sample preparation procedure.

Method detection limit (MDL) – The minimum concentration of a substance that can be measured and reported with 99% confidence that the analyte concentration is greater than zero. The MDL is determined from analysis of a sample in a given matrix containing the analyte which has been processed through the preparative procedure.

Quality Control Sample (QCS) – A solution of method analytes of known concentrations which is used to fortify an aliquot of LRB or sample matrix. The QCS is obtained from a source external to the laboratory and different from the source of calibration standards. It is used to check either laboratory or instrument performance.

Sample holding time – The storage time allowed between sample collection and sample analysis when the designated preservation and storage techniques are employed.

Sensitivity – The slope of the analytical curve, *i.e.* functional relationship between emission intensity and concentration.

Water Sample – a sample taken from one of the following sources: drinking, surface, ground, storm runoff, industrial or domestic wastewater